

Automatic Strapping Machine

The JK-5000 is a proven arch machine of Strapack performance available in an affordable price.

- **Compact Body**
Space-efficient design with internal reel unit utilizing a standard size strap coil.
- **Strapping Speed**
Standard strapping rate is 37 straps/min, even with tension applied. The machine is ready to operate in less than 25 seconds.
- **Easy strap width conversion**
The JK-5000 can be set up to run 5mm to 12mm polypropylene strap with simple adjustment. No conversion parts are required.
- **Energy Saving**
To conserve energy and reduce wear, the JK-5000 automatically shuts off the motor while maintaining proper heater temperature when it has not been cycled for 30 seconds. Depressing the Start Button re-starts the motor and applies the strap.
- **Jam Resistant**
The JK-5000 automatically re-feeds the strap when a mis-feed occurs. The strap will not jam on the slide table when the machine is cycled with no package.



JK-5000

Standard Specifications (Arch size 650 mm wide x 500 mm high)

Dimension	Width	921 mm
	Height	1436 mm
	Depth	600 mm
	Weight	115 kg
Table Height		827 mm
Package Size	Max	W 620 X H 480 mm
	Min	W 60 X H 30 mm
Joint / Strap		heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm
Strap Tension		330 N (33 kgf) or 300 mm stroke
Power Supply		100, 120, 220, 230, 240V Single phase 50/60Hz 0.65kVA

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2020 Strapack Corporation

DISTRIBUTED BY:



ISO 9001 and 14001 Certified

STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone 81-3-6278-1806 Fax. 81-3-6278-1807
(URL) <http://www.strapack.com> (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone: 1-510-475-6000 Fax: 1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone: 32-3-355-1520 Fax: 32-3-355-1521