







TG1140

A high performing Cut A close fitting and flexible glove with a MicroDex Nitrile Foam palm dipped coating. Provides excellent grip in wet dry and oily conditions.

Key Features

- Fine gauge Polyamide liner offering outstanding dexterity
- A glove of choice for those with sensitive skin as OEKO-TEX®approved
- MicroDex coating makes it suitable for dry, damp and oily conditions

Ideal for

- Fine assembly work
- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Warehousing and Logistics
- Waste, Recycling and Local Authority

Sizes:	6-11	Gauge:	15gg	
Liner:	Polyamide	Coating:	MicroDex Ultra	
No/Bag:	10	No/Carton:	200	





TG1140

Glove Specifications

Glove lengths 220mm-270mm

Glove Weight 15 gauge

Liner Type Polyamide

Glove colour Pantone 1795c / R:223 G:59 B:48 / C:8 M:96 Y:100 K:1

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN


Coating Specifications

Coating colour Black

Dip type MicroDex Nitrile

Dip Application Palm Dipped

Glove Treatment MicroDex



Carton Dimensions

400mm x 520mm x 450mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.



www.traffiglove.com